



| Bearing No. | Boundary dimensions | | | Basic load ratings(kN) | | Limiting speed | | Mass kg |
|-------------|---------------------|-----|----|------------------------|--------|----------------|-------|------------|
| | mm | | | Dynamic | Static | rpm | | |
| | d | D | B | Cr | Cor | Grease | Oil | |
| 7406AC | 30 | 90 | 23 | 55.6 | 32.7 | 6,500 | 8,500 | 0.96 |
| 7407AC | 35 | 100 | 25 | 66.4 | 41.9 | 5,500 | 8,000 | 1.14 |
| 7408AC | 40 | 110 | 27 | 73.7 | 42.1 | 5,200 | 7,000 | 1.4 |
| 7409AC | 45 | 120 | 29 | 84.5 | 55.1 | 5,000 | 6,500 | 1.8 |
| 7410AC | 50 | 130 | 31 | 115.8 | 78.3 | 4,500 | 6,000 | 2.25 |
| 7411AC | 55 | 140 | 33 | 121.4 | 84.5 | 4,200 | 5,600 | 2.75 |
| 7412AC | 60 | 150 | 35 | 131.8 | 95.3 | 3,800 | 5,200 | 3.4 |
| 7413AC | 65 | 160 | 37 | 142.5 | 106.7 | 3,400 | 4,800 | 4.2 |
| 7414AC | 70 | 180 | 42 | 154.6 | 122 | 3,200 | 4,500 | 5.8 |
| 7415AC | 75 | 190 | 45 | 165.2 | 133.5 | 3,000 | 4,200 | 7 |
| 7416AC | 80 | 200 | 48 | 176.5 | 147.2 | 2,800 | 4,000 | 8.4 |
| 7417AC | 85 | 210 | 52 | 188 | 161.5 | 2,600 | 3,700 | 9.6 |
| 7418AC | 90 | 225 | 54 | 200.3 | 178.1 | 2,400 | 3,400 | 11.2 |