


Stainless Steel Four Point Angular Contact Ball Bearing



Bearing Number	Dimensions in Inches				Capacities [lbs]				Torque [in-lbs]		Weight [lbs]
	Bore	Outside Dia.	L1	L2	Radial		Axial		Static	Dynamic	
					Dynamic	Static	Dynamic	Static			
SAA10XL0	1.000	1.375	1.14	1.235	290	247	730	370	170	110	0.026
SAA15XL0	1.500	1.875	1.64	1.735	400	296	1,000	460	340	187	0.039
SAA17XL0	1.750	2.125	1.89	1.985	460	319	1,140	500	440	232	0.045
SA020XP0	2.000	2.5	2.186	2.314	680	514	1,710	790	770	434	0.1
SA025XP0	2.500	3	2.686	2.814	830	583	2,090	910	1,150	601	0.13
SA030XP0	3.000	3.5	3.186	3.314	990	643	2,470	1,010	1,600	785	0.15
SA035XP0	3.500	4	3.686	3.814	1,140	701	2,850	1,110	2,130	986	0.18
SA040XP0	4.000	4.5	4.186	4.314	1,290	756	3,220	1,210	2,740	1,205	0.19
SB020XP0	2.000	2.625	2.231	2.393	930	758	2,340	1,130	1,080	658	0.16
SB025XP0	2.500	3.125	2.731	2.893	1,140	848	2,840	1,290	1,600	895	0.19
SB030XP0	3.000	3.625	3.231	3.393	1,340	933	3,350	1,440	2,220	1,159	0.24
SB035XP0	3.500	4.125	3.731	3.893	1,540	1,014	3,860	1,590	2,940	1,450	0.27
SB040XP0	4.000	4.625	4.231	4.393	1,750	1,091	4,370	1,720	3,770	1,764	0.3