


## CRBH High Rigidity crossed roller bearing



Identification	Identification	Shaft diameter(mm)	Main dimensions(mm)				Mounting dimensions(mm)		Basic dynamic load rating(N)	Basic static load rating(N)	weight(kg)
			d	D	B	r/min	da	Da			
CRBH208A	CRBH208AUU	20	20	36	8	0.3	24	31	2910	2430	0.04
CRBH258A	CRBH258AUU	25	25	41	8	0.3	29	36	3120	2810	0.05
CRBH3010A	CRBH3010AUU	30	30	55	10	0.3	36.5	48.5	7600	8370	0.12
CRBH3510A	CRBH3510AUU	35	35	60	10	0.3	41.5	53.5	7900	9130	0.13
CRBH4010A	CRBH4010AUU	40	40	65	10	0.3	46.5	58.5	8610	10600	0.15
CRBH4510A	CRBH4510AUU	45	45	70	10	0.3	51.5	63.5	8860	11300	0.16
CRBH5013A	CRBH5013AUU	50	50	80	13	0.6	56	74	17.3	20.9	0.29
CRBH6013A	CRBH6013AUU	60	60	90	13	0.6	66	84	18.8	24.3	0.33
CRBH7013A	CRBH7013AUU	70	70	100	13	0.6	76	94	20.1	27.7	0.38
CRBH8016A	CRBH8016AUU	80	80	120	16	0.6	88	112	32.1	43.4	0.74
CRBH9016A	CRBH9016AUU	90	90	130	16	0.6	98	122	33.1	46.8	0.81
CRBH10020A	CRBH10020AUU	100	100	150	20	0.6	110	140	50.9	72.2	1.45
CRBH11020A	CRBH11020AUU	110	110	160	20	0.6	120	150	52.4	77.4	1.56
CRBH12025A	CRBH12025AUU	120	120	180	25	1	132	168	73.4	108	2.62
CRBH13025A	CRBH13025AUU	130	130	190	25	1	142	178	75.9	115	2.82
CRBH14025A	CRBH14025AUU	140	140	200	25	1	152	188	81.9	130	2.96
CRBH15025A	CRBH15025AUU	150	150	210	25	1	162	198	84.3	138	3.16
CRBH20025A	CRBH20025AUU	200	200	260	25	1	212	248	92.3	169	4
CRBH25025A	CRBH25025AUU	250	250	310	25	1.5	262	298	102	207	4.97