


## Double-row taper roller bearings with outer spacer ring



847000

Bearing designation	Dimensions(mm)						Load factor				Load ratings(N)		Limiting rotational speed, min-1 Grease	Mass(kg)	
	d	D	T	B	C	r1,2min	r3,4min	e	Y1	Y2	Y0	Cr			Cor
847713	66.675	177.8	114.3	107.95	37.308	1	3.3	0.8	0.85	1.26	0.83	578000	828000	2000	14.89
847719	95.25*	190.5*	114.3	115.062	44.45	0.5	3.3	0.42	1.61	2.4	1.58	614000	1260000	1900	16.26
347920M	100.211*	168.275*	95.25	95.25	30.162	0.8	3.3	0.47	1.43	2.12	1.4	429000	797000	1600	8.73
347944M	219.075*	358.775*	196.85	200.025	85.725	1.5	6.4	0.33	2.03	3.02	2.03	2240000	4880000	700	91.732
847967XMY	333.375*	469.9*	166.688	166.688	71.438	3.3	3.3	0.33	2	3	1.97	2400000	5910000	630	94.7
847967JMY	333.375*	469.9*	166.688	166.688	71.438	3.3	3.3	0.33	2	3	1.97	2150000	5220000	630	236.42
40471/500XJM	500	720	217	185	75	6	6	0.82	0.82	1.23	0.81	2846000	6807000	260	236.42
537905C17	25	52	37	18,5	37	0,60	1,0	0,37	1,80	2,68	1,76	58500	75000	5000	0,367
537906E1C35	30	60	37	18,5	37	3,10	0,2	0,43	1,55	2,30	1,50	64800	90100	5000	0,476
537907C17	34	64	37	18,5	37	3,30	1,0	0,47	2,21	3,29	2,16	68600	99800	3700	0,556
537707C17	35	64	37	18,5	37	3,56	1,2	0,47	1,43	2,13	1,40	68600	99800	3700	0,556
537807C17	35	68	37	18,5	37	2,50	1,0	0,51	1,33	1,97	1,30	69800	105000	3700	0,614
537908C17	37	72	37	18,5	37	3,30	1,0	0,43	1,57	2,34	1,53	81600	112000	3700	0,718
537808C17	39	68	37	18,5	37	2,80	1,0	0,51	1,33	1,97	1,30	69800	105000	3700	0,546
537708C17	39	72	37	18,5	37	3,80	1,0	0,50	1,30	1,97	1,29	69800	105000	3700	0,673
537909K1C17	49	84	43	21,5	43	3,3	1,5	0,46	1,47	2,19	1,44	108000	156000	3200	0,941
537909K2C17	49	84	43	21,5	43	3,3	1,5	0,46	1,47	2,19	1,44	108000	156000	3200	0,941
537909KC17	49	84	43	21,5	43	3,3	1,0	0,45	1,49	2,23	1,46	108000	156000	3200	0,941
537910C17	50	84	54	27	54	4,5	1,0	0,5	1,47	2,20	1,44	108000	156000	3200	1,041
537810AC17	50	92	55	27,5	55	1,5	1,2	0,42	1,61	2,39	1,57	157000	232000	3200	1,543