


## Large Angular Contact Ball Bearing



Bearing Designation			Dimensions(mm)					load rating		action spot	load rating		installation dimension					Weight
Single row	Pairs DF	DB	d	D	B	r1	r	Single row Cr	C0r	mm a	Pairs C	C0r	da min	Da max	Db max	ra max	r1a max	Kg ≈
71834 C	DB	DF	170	215	22	1.1	0.6	75	100	36.8	125	205	177	208	211	1	0.6	1.88
71834 AC	DB	DF	170	215	22	1.1	0.6	70	95	36.8	115	190	177	208	211	1	0.6	1.88
71834 B	DB	DF	170	215	22	1.1	0.6	60	80	36.8	100	160	177	208	211	1	0.6	1.88
71934 C	DB	DF	170	230	28	2	1	115	145	40.8	185	285	180	220	224	2	1	3.29
71934 AC	DB	DF	170	230	28	2	1	110	135	40.8	175	270	180	220	224	2	1	3.29
71934 B	DB	DF	170	230	28	2	1	90	110	40.8	150	225	180	220	224	2	1	3.29
7034 C	DB	DF	170	260	42	2.1	1.1	200	225	49.8	320	445	181	249	254	2	1	7.65
7034 AC	DB	DF	170	260	42	2.1	1.1	185	210	49.8	305	425	181	249	254	2	1	7.65
7034 B	DB	DF	170	260	42	2.1	1.1	160	185	49.8	260	365	181	249	254	2	1	7.65
7234 C	DB	DF	170	310	52	4	1.5	305	360	58.2	495	720	187	293	301	3	1.5	17.5
7234 AC	DB	DF	170	310	52	4	1.5	290	345	58.2	475	685	187	293	301	3	1.5	17.5
7234 B	DB	DF	170	310	52	4	1.5	255	300	58.2	415	600	187	293	301	3	1.5	17.5
7334 C	DB	DF	170	360	72	4	1.5	410	505	71.5	665	1010	187	343	351	3	1.5	36
7334 AC	DB	DF	170	360	72	4	1.5	390	485	71.5	635	970	187	343	351	3	1.5	36
7334 B	DB	DF	170	360	72	4	1.5	345	430	71.5	565	860	187	343	351	3	1.5	36
71836 C	DB	DF	180	225	22	1.1	0.6	75	105	38.1	125	210	187	218	221	1	0.6	1.98
71836 AC	DB	DF	180	225	22	1.1	0.6	75	100	38.1	120	200	187	218	221	1	0.6	1.98

## Large Angular Contact Ball Bearing

71836 B	DB	DF	180	225	22	1.1	0.6	60	85	38.1	100	165	187	218	221	1	0.6	1.98
71936 C	DB	DF	180	250	33	2	1	145	180	45.3	235	360	190	240	244	2	1	4.87
71936 AC	DB	DF	180	250	33	2	1	135	170	45.3	225	340	190	240	244	2	1	4.87
71936 B	DB	DF	180	250	33	2	1	115	140	45.3	190	280	190	240	244	2	1	4.87
7036 C	DB	DF	180	280	46	2.1	1.1	225	265	53.8	365	525	191	268	274	2	1	10
7036 AC	DB	DF	180	280	46	2.1	1.1	215	250	53.8	345	500	191	268	274	2	1	10
7036 B	DB	DF	180	280	46	2.1	1.1	185	220	53.8	300	435	191	268	274	2	1	10
7236 C	DB	DF	180	320	52	4	1.5	315	380	59.5	510	755	197	303	313	3	1.5	18
7236 AC	DB	DF	180	320	52	4	1.5	300	360	59.5	485	725	197	303	313	3	1.5	18
7236 B	DB	DF	180	320	52	4	1.5	260	315	59.5	420	630	197	303	313	3	1.5	18
7336 C	DB	DF	180	380	75	4	2	440	560	75	715	1125	197	363	369	3	2	42
7336 AC	DB	DF	180	380	75	4	2	425	540	75	685	1080	197	363	369	3	2	42
7336 B	DB	DF	180	380	75	4	2	375	480	75	610	960	197	363	369	3	2	42