


RU Crossed roller bearing



Identification number	Main dimensions						Shoulder height		Basic load rating \square radial \square		Weight KG
	ID	OD	PCD	Height	Oil hole	rmin	ds	Dh	C	Co	
	d	D	dp	B	d1				kN	kN	
RU28	10	52	28	8	-	0.3	24	29.5	2.9	24	0.12
RU42	20	70	41.5	12	3.1	0.6	37	47	7.35	8.35	0.29
RU66	35	95	66	15	3.1	0.6	59	74	17.5	22.3	0.62
RU85	55	120	85	15	3.1	0.6	79	93	20.3	29.5	1
RU124(G)	80	165	124	22	3.1	1	114	134	33.1	50.9	2.6
RU124X	80	165	124	22	3.1	1	114	134	33.1	50.9	2.6
RU148(G)	90	210	147.5	25	3.1	1.5	133	162	49.1	76.8	4.9
RU148X	90	210	147.5	25	3.1	1.5	133	162	49.1	76.8	4.9
RU178(G)	115	240	178	28	3.1	1.5	161	195	80.3	135	6.8
RU178X	115	240	178	28	3.1	1.5	161	195	80.3	135	6.8
RU228(G)	160	295	227.5	35	6	2	208	246	104	172	11.4
RU228X	160	295	227.5	35	6	2	208	246	104	172	11.4
RU297(G)	210	380	297.3	40	6	2.5	272	320	156	281	21.3
RU297X	210	380	297.3	40	6	2.5	272	320	156	281	21.3
RU445(G)	350	540	445.4	45	6	2.5	417	473	222	473	35.4
RU445X	350	540	445.4	45	6	2.5	417	473	222	473	35.4